

# LAUFEN INSTALLATION SYSTEM

## CWNL100 Concealed frame with cistern for wallhung WC 92710.0



### TECHNICAL DATA

Order no.	92710.0	Mounting acc. incl.	Wall bracket, protection box for access opening, inspection box for WC connection, retaining bolts with protection plugs, angle valve R 1/2, PEX pipe connection kit Ø 15, Ø 16 mm, WC connector 90° (Ø 90 mm), PE transition sleeve Ø 90 / 110 mm, WC connection set Ø 90 mm, L=180 mm, mounting material.
Certified to	EN 14055 CL1	Mounting acc. excl.	Fastening set for wall, order no. 89563.5 (Norway) Sound insulation set
matching for	All LAUFEN wallhung toilets	Accessories excl.	Actuator plates dual flush, order no. 90010.0, 90010.1, 90010.2 (glass), 90010.3 (stainless steel), 90010.4, 90010.5, 90010.6, Electronic actuator plate dual flush, order no. 90010.7 (glass)
Specifications	Self-supporting steel frame for covering with plasterboard, installation onto a solid wall, in drywall constructions. For front/top operated. Dual-Flush 6/3-l (4.5/3-l-flush), with water condensation insulation. Fill valve Noise Class I.	Mounting information	Height from finished floor to top of WC pre-set to 400 mm.
Other specifications	Galvanized leg supports, rotatable, height-adjustable 0-200 mm. Capable to resist 400 kg	Colours	Surface powder coated blue
Water inlet	side left, PEX pipe connection kit Ø 15, Ø 16 mm		
Outlet	DN 90/110		
Flow pressure range	0.5-10 bar		
Water temperature	max. 25°C		
Tank	Installation depth: 120 mm material PP		
Installation depth	155-205 mm		
Weight	8,2 kg		

### TECHNICAL DRAWINGS / S 1 : 20

